

ROTARY COMPRESSORS | AIR TREATMENT | AFTERMARKET

# **Total Solution Provider**



# Gardner Denver

provides the broadest range of air compressors and air treatment solutions to handle a wide-variety of applications. From the most demanding, requiring compressed air 24/7/365 to the fluctuating day-to-day or shift-to-shift, we have the right compressed air equipment to maximize productivity and energy savings.





# FIXED SPEED | OIL-FLOODED ROTARY COMPRESSORS





#### Versatile

- 2-15 HP
- 100-150 PSIG
- 5-50 CFM



**L Series** 

# Simplistic

- 5-400 HP
- 75-190 PSIG
- 13-1604 CFM



**Electra-Saver II G2** 

#### Slow Speed Reliability

- 40-300 HP
- 100-200 PSIG
- 137-1541 CFM



# Electra-Saver/G2

#### Turn-Valve Efficiency

- 75-500 HP
- 100-200 PSIG
- 342-2459 CFM



#### **Electra TS**

#### Market-Leading Efficiency

- 200-300 HP
- 100-200 PSIG
- 1092-1639 CFM

# VARIABLE SPEED | OIL-FLOODED ROTARY COMPRESSORS



# **LRS Series**

#### Energy Efficiency

- 7-290 kW
- 75-190 PSIG
- 29-1620 CFM



# **Electra TSV**

#### Ultimate Efficiency

- 150-225 kW
- 100-200 PSIG
- 1178-1652 CFM

# **OIL-FREE | COMPRESSORS**



# EnviroAire S & ES

- 3-10 HP
- 116-140 PSIG
- 8-126 CFM



# EnviroAire VS

- 15-37 kW
- 75-145 PSIG
- 65-242 CFM



EnviroAire T & TVS

- 37-74 kW
- 115-145 PSIG
- 186-411 CFM



Ultima

- 75-160 kW
- 75-145 PSIG
- 247-842 CFM



# PureAir T & TVS

- 90-160 kW
- 110-155 PSIG
- 597-919 CFM



# PureAir T & TVS

- 185-355 kW
- 110-155 PSIG
- 1141-1902 CFM

# REFRIGERATED DRYERS

#### **RPC Series**

#### Energy Saving

- 75-2,000 CFM
- Latest Advancement in Heat Transfer Technology

# **RHT/GHRN Series**

#### High Temp

- 20-132 CFM
- Up to 180°F Inlet Temperature

#### **RHP**

#### High Pressure

- 30-3,000 CFM
- Up to 725 PSIG Inlet Pressure

# **XGNC Series**

#### Non-Cycling

- 7-1,200 CFM
- 1,800-12,000 CFM Modular

#### **RGD Series**

#### Non-Cycling

- 2.5-1.200 CFM
- Air-Cooled
- 2-Year Warranty

#### **GNC Series**

#### Non-Cycling

■ 10-650 CFM

# **GSRN Series**

#### Non-Cycling

- 10-2,250 CFM
- Air-Cooled and Water-Cooled
- Stainless Steel Components

#### **GTRC Series**

#### Cycling Dryer

- 100-2,250 CFM
- Adjustable Dew Point
- Stainless Steel Components

# **XGCY Series**

#### Cycling Dryer

■ 10-24,000 CFM

# **DESICCANT DRYERS**

#### **DGH Series**

#### Heatless

- 3-5.400 CFM
- Dew Point to -100°F

# **DHP/GEHD Series**

#### Externally Heated

- 100-4,000 CFM
- Dew Point to -40°F

# **DPB/GBPD Series**

#### Blower Purge

- 100-4.300 CFM
- Dew Point to -40°F

#### **XGHB Series**

# Heated Blower

- 150-8,000 CFM
- Dew Point to -40°F

# **DHC Series**

# Heat of Compression

- 350-10,000 CFM
- Dew Point Demand Control

#### **XGHP Series**

#### Heated Purge

- 150-8.000 CFM
- Dew Point to -40°F

# **XGML Series**

# Modular Desiccant

- 3-177 CFM
- -40°F & -100°F Dew Point

#### **XGHL Series**

#### Heatless

- 90-5,000 CFM
- Dew Point to -100°F

# MEMBRANE DRYERS, NITROGEN GENERATORS, CHILLERS, FILTERS, PIPING, LUBRICANTS, & CONDENSATE MANAGEMENT

# **Membrane Dryers**

# MES/MMD Series

- 1.5-138 CFM
- Dew Point to -40°F

# **Filters**

#### XG/FIL/GIL Series

- 20-21,250 CFM
- High Pressure and High Temperature Filters Available

#### **Drains**

#### XGDR/SMD/DS/EDDS Series

- Zero-Loss
- Electric Timed Drain

# **Mist Eliminators**

#### XG/FME Series

- 125-10.000 CFM
- Mist Eliminator

#### **Piping**

#### Quick-Lock & Big Lock Series

- Sizes from 0.5-10"
- Extruded Aluminum Piping
- All Metal Fittings

# **Oil/Water Separators**

# GD PAK/CTS/CTS-T Series

 Effectively Treats Contaminated Condensate

# Intelli-PAK

- Cabinet PAK Design
- Proprietary Tank Connections

# **Nitrogen Generators**

#### XGN2 Series

- Membrane 1-153 CFM, 95-99.5% purity
- PSA 15-2,353 CFM, 95-99.999% purity
- High Pressure

#### **GDN2 Series**

- 98-99.999% Purity
- Skid-Mounted PSA Design

# Lubricants

# AEON Lubricant

- 8,000 Hr Synthetic Blends
- Food Grade Available
- High Temperature Blends

#### Other

# XGCH Series - Process Chillers

- 0.5-106.0 Ton
- 113°F Ambient Standard

#### XGTK Series - Air Storage Tanks

- Vertical & Horizontal
- 30-5,000 gal Standard

#### XGCT - Activated Carbon Towers

■ 80-5,500 CFM



The leader in every market we serve by continuously improving all business processes with a focus on innovation and velocity



1800 Gardner Expressway Quincy, IL 62305 www.gardnerdenver.com









©2024 Industrial Technologies and Services, LLC Printed in U.S.A. GS-LINE 17th Ed. 7/24

